

WEEKLY BULLETIN NO. 2012/14
DUE ON 28 /12/2012 at 11:00 HOURS.
IMPORTANT NOTES TO TENDERERS: -

1. All tenderers should quote exactly as per Railways requirement separately for each item.
2. All tenderers should note that the drawings, specifications, samples if required, same can be given by this office / consignee. **Drawing are also attached herewith.**
3. Ex. Stock delivery will be preferred. Rate should be quoted for the delivery at consignee`s end.
4. Firms registered with Sr. DMM / Mumbai, Central Railway, Production Units and RDSO are eligible to submit their offer against this tender otherwise Sr. DMM Mumbai will have the right to accept / reject the tender without assigning any reason.
5. Vendor must give the copy of MRP / Price list along with their quoted price for branded items. (Separate rate should be quoted for individual brand).
6. Suppliers should invariably mention their sales tax registration No. on their quotations, failing which their offer will be summarily rejected.
7. This bulletin is available on <http://www.cr.indianrailways.gov.in>

No	Tender No.	Description	Qty.	Unit	Consignee.
1	92.12.5222	High power two zone PA Amplifier capable of delivering 200 watts output power from each zone total 400 watts of Model No.tza-4000 of Ahuja make Philips, Yamaha, or Bosch make.	3	Nos	SSEE/Tele/Stores/CLA
2	92.12.5548	Pole pruner Amp 65 manual (Agremate) Extendable length 2365-6500mm, Length Adjustment 7 stages with 16" tooth curved saw 6.5m, 2.55 Kgs.	7	Nos	SSE (OHE) CLA
3	92.12.5550	Wooden Trestle for OHE Drg.No.ET/SO/2725R-4.	8	Nos	SSE (OHE) CLA
4	92.12.5565	GOOT make Portable Desoldering station Model TP100AS type WELLER make or similar.	1	No.	SSE/Sig/CLA
5	92.12.5566	Single channel microcontroller based earth resistance sensing unit specification I) Input working voltage: 110 V AC+/- 15% II) Rated voltage of Network to be monitored: 12V to 150 V DC. III) Measuring Instrument: Microcontroller. IV) Maximum Permissible stray DC voltage: 200V DC V) Indicating device: L.C.D. Display (indicate leakage resistance directly in K ohms of both + (Positive & negative poles. VI) DC internal resistance: more than 100 K ohms. VII) Operating value 1 K Ohm. VIII) Alarm: Audiovisual alarm. IX) Housing: M.S. X) Connections: 2.5 sq.mm wire.	11	Nos.	SSE/SIG/STO/KYN
6	92.12.5592	Air circulating wall bracket fan 600 mm 24" sweep 250 volts.1400 RPM, single phase without regulator, 3 blades, 50Hz.conf to IS 2997 of 1964.As per Bajaj cat No. Supreme or CGL cat.No.AC 600 wall-I. Make :Bajaj ,CGL, Almonard.	20	Nos	Sr.SEE(M)CSTM.

7	92.12.5593	Metal halide lamp double ended 150 W,230 Volts R 75 base cap. Suitable for 230V/250 V AC supply. Make - Philips, Anchor. As per Philips item No.MHN-TD or similar.	300	Nos	Sr.SEE(M)CSTM.
8	92.12.5594	Fibre glass step trestle ladder 10' feet long, Non conductive fibre glass rail with fully separated aluminium step on front and back step width 3", bottom width 26"approx spread 67".Approx weight 20 kgs.	6	Nos	Sr.SEE(M)CSTM.
9	92.12.5595	Street light fitting 1x 36 watts 230 volts AC deep drawn single piece aluminum housing anodised inside and acrylic cover. As per Bajaj cat. No. BJS LA 136CFL. Make: Bajaj, CGL, Havells.	100	Nos	Sr.SEE (M) CSTM.
10	92.12.5596	Distribution Board single phase 8 way (super plus SPN DBS double door) Powder coated sheet steel enclosure fitted with bus bar din and neutral bar, earth bar, door earthing IP-43 protection. As per cat.No.NSPEDD08. Make: Indo Asian, L&T, Havells conf.to IS 13032.	100	Nos	Sr.SEE (M) CSTM.
11	92.12.5597	Storage battery lead acid 12 volts 180AH capacity at 20 hours, rate of discharge at 27 degree C, dimension as per IS 7322/74 latest. Make :Exide, EMCO, Kirloskar.	6	Nos	SSE (OHE) CLA
12	92.12.5489	R.C.C. pipe half round 100mm IS. 458 or latest.Size:100mm x 1 Meter length.	200	Nos.	SSE/Cable/CLA
13	92.12.5538	T5 Lamp 2' long ,14 watts, 230 volts, colour temperature 2700K (Yellow Colour) as per Havells cat. No. PHST27114399.Make:Havells,Bajaj,CGL.or similar	900	Nos.	Sr.SEE(M)CSTM.
14	92.12.5539	Compact fluorescent Lamp 26 watts cross pin 240 volts colour temperature 2700K (Yellow Colour).As per Havells cat. No. PHCD*#026. Make :Havells, CGL, Philips. or similar	630	Nos.	Sr.SEE(M)CSTM.
15	92.12.5540	Electronic Ballast suitable for 2x 14 watts T5 Lamp 230 volts. As per Philips cat.No.SAP-913702242412.Make Philips, Havells type EBE 214 TL5.,Make GE.or similar	130	Nos.	Sr.SEE(M)CSTM.
16	92.12.5606	Electrolytic condenser can type 1000 MFD 100Volts surge voltage 120 Volts make Rescon Alcon, Keltron or similar.	300	Nos.	SSE(S/Store) KYN
17	92.12.5607	Electrolytic condenser can type 1500 MFD 100Volts surge voltage 120 Volts make Rescon Alcon, Keltron or similar.	300	Nos.	SSE(S/Store) KYN
18	92.12.5608	Electrolytic condenser can type 500 MFD 100Volts surge voltage 120 Volts make Rescon Alcon, Keltron, or similar.	300	Nos.	SSE(S/Store) KYN
19	92.12.5613	Dragon Search Light as per Specification Enclosed Model SLD-01 or Similar. (Specification attached)	20	Nos	SSE(S/Store) CLA
20	92.12.5615	Printer HP Laser jet M1216nfh MFP or similar.	1	No.	Sr.DEE(TD)CSTM
21	92.12.5616	PBT Motor terminal Siemens suitable for Siemens motor as per geared motor assembly drg. No. 1F- 5509-00-0209594-001 and to be used in 110V DC	500	Nos.	SSE(S) CLA

22	92.12.5617	Cable PVC flexible 36/0.6 Finolex strand 2.5 sq.mm for wiring for point machine in Red- 500 Mtrs, White - 500 Mtrs. Blue- 500 Mtrs. Yellow - 600 Mtrs. Black - 400 Mtrs. Grey - 500 Mtrs. & Brown - 500 Mtrs of Zenium or similar make	3500	Mtrs.	SSE(S) CLA
23	92.12.5618	Handle for Point Motor make of seamless tube duly welded and Galvanized.	400	Nos.	SSE(S) CLA

TENDER No 92-12-5613

Specifications for Dragon Search Light

- Operating range 1000 Mtrs (One Km.)
- High powered Halogen Lamp 55 watts
- Deep Parabolic Reflector
- Single Push to ON switch
- Tough, Water proof & impact resistant body
- SMPS Inbuilt Charger
- All models have low battery protection
- Size and shape of all models are same
- Operating Temperature -30 C to 55 C
- Long Operating Time on Single charge for 80 minutes
- Portable, light weight having shoulder pad and a handle
- Intensity of light can be increased or decreased by dimmer switch
- Works on maintenance free chargeable Lead-Acid battery 12 V, 7 Ah
- Variable timer and Auto Flashing
- Microprocessor based Technology
- Membrane Touch Switches
- LCD Display
- Single Moulded cabinet with integral handle

Inbuilt SMPS Battery Charger

Battery charger works on 220 volts 50 Hz supply. Auto cut-off circuit is provided to avoid overcharging of the battery. Lead with 3 pin male charging connector is provided to connect the same with 3 pin female charging socket provided in battery container. AC and DC fuse holders are provided with Red LED to indicate fuse due to AC and DC failure respectively.

Features

Single push to ON switch for flashing, 0 to 60 seconds for timer (adjustable) and continuous mode for 80 minutes in one charge, having three position selector switch, Light can be dimmed by Dimmer switch, also having Auto flashing, Variable Timer and Inbuilt SMPS Charger.

Dimensions: Length: 25cms; Front Diameter: 17cms; Rear Diameter: 13cms; Weight of Light: 4 Kgs.

व. मं. सि. एच. दूय इंजी (दग्गि)
मध्य रेल, मुम्बई सीएसटी
SR. DSTE. (S) C. RLY. CSTM